

## ICC Votable Proposal Submission

*Title of proposal*

Coding-independent code points (CICP) for video signal type identification

*To discuss:*

- *Does this give us a robust workflow?*
- *Is ICC profile the right place? Versus a TIFF or PNG tag or XMP?*
- *Provide more workflow details*
- *√ Keep YCbCr!*
- *√ Call it CICP instead of VUI!*
- *√ Mention other equivalent color space types (SMPTE ULs...)*
- *Add links to background docs describing video workflows?*

### Proposers:

*Names and member companies of proposers*

Lars Borg, Adobe

Chris Seeger, NBCU

### Submission date:

*Date of submission to ICC Technical Secretary for distribution to membership*

TBD

## 1. Introduction

*Outline of proposal, its motivation and context*

### A summary

This proposal enables the linking of an ICC profile with an equivalent video signal type identification (CICP) representation.

### The problem to be solved

There is currently no best practice for linking the color space encoding represented by an ICC profile with an equivalent video signal type identification (CICP) used in video equipment compliant with ITU-T H.273 and ITU-T H.265 as defined by the International Telecommunication Union (ITU) or as defined by SMPTE Universal Labels.

There is no best practice for reliably exchanging still images between graphics workflows and video workflows using the correct color space.

There is no best practice for integrating ICC-tagged still images into video presentations and rendering these stills the same way as the video is rendered.

In video equipment, a video frame can be processed as scene-referred or display-referred as needed and as prescribed by video standards, but ICC profiles allow only one such processing option per ICC profile.

## The solution

The proposal adds an optional CICIP tag, which includes the Coding-independent code points (CICIP) for the profile's effective color image encoding. The proposal is applicable to Input and Display profiles using the RGB or YCbCr color models.

## The application

A processor receiving media with a CICIP tag can use the CICIP tag to switch its color processing from using the ICC profile to using its video color processor. This enables the processor to render ICC-tagged content the same way that untagged video is rendered, thus providing seamless integration with video-based processing such as gamut and tone mapping and other features of its video color processor.

A video frame grabber can save the video frame as RGB or YCbCr with an embedded ICC profile and embedded CICIP tag.

When saving as YCbCr, the frame is in the same color space as the original video and can be re-inserted into the same video type without any loss. The ICC profile provides an approximate color rendering (typically display-referred) for non-video equipment, while the CICIP tag provides the mapping back to the original video space.

When saving as RGB, the frame is typically converted from the video's narrow range YCbCr format to full range RGB of the same color space, placing black at 0. This facilitates editing in image applications. The ICC profile provides an approximate color rendering (typically display-referred) for the graphics application, while the CICIP tag enables converting back to the original video space.

## Issues

### *Identify shortcomings*

What can go wrong?

- Using the CICIP tag can result in a different color appearance versus using the ICC profile. What happens if this image and profile propagates into print publishing, PDF, web pages, where only some apps support the CICIP tag?

## 2. The acceptance of this proposal will result in:

### *Summary of proposed changes to ICC specifications and (where required) CMM behavior*

The proposal extends ICC.1 Version 4 by defining an optional Version 4 tag (cicpTag) and corresponding tag type (cicpType).

There are no required changes for CMMs.

## 3. Nature of the proposal

### *State whether tag or type(s) are being proposed, the effect on ICC resources such as registries, and consequence for ICC specification versions*

The proposal extends ICC.1 Version 4 by defining an optional Version 4 tag (cicpTag) and corresponding tag type (cicpType).

This proposal does not impact ICC registries.

#### **4. Votable Proposal**

*Full description of proposal*

See next main section below.

#### **5. Applications and Workflows**

*Usage scenarios envisaged as a result of the proposal*

Workflow would include:

- Input to post-production editor, composer, 3D software, still graphics editor
  - ICC CICIP tag detected, transform applied to conform to the video space of the timeline or working space's color volume
- Input into Still Store (for static graphics playback)
  - ICC CICIP tag detected, transform applied to preset still-store broadcast working space
- Input to web browser for compositing and rendering
  - ICC CICIP tag detected from source graphic, broadcast video tag is detected, graphic is mapped properly into desktop working space

EXAMPLE:

Video - frame grab - PNG - editing, masking, adding text... - PNG - insert in video

# CICIP Tag and Type proposal

√ Change VUI to CICIP! Retain YCbCr!

## 1.1.1.1 Normative References

Recommendation ITU-T H.273 (12/2016), Coding-independent code points for video signal type identification, <https://www.itu.int/rec/T-REC-H.273/en>

## 1.1.1.2 Abbreviated terms

CICIP Coding-independent code points for video signal type identification

## 1.1.1.3 cicpTag

Tag signature: 'cicp' (63696370h)

Permitted tag type: cicpType

This tag defines Coding-independent code points for video signal type identification (CICIP).

The color image encoding specified by the CICIP tag content shall be equivalent to the color image encoding represented by this ICC profile.

This tag may be present when the data colour space in the profile header is RGB or YCbCr, and the profile class in the profile header is Input or Display. The tag shall not be present for other data colour spaces or profile classes indicated in the profile header.

## 1.1.1.4 cicpType

The cicpType specifies Coding-independent code points for video signal type identification. The byte assignment and encoding shall be as given in Table 1~~Table 1~~.

**Table 1 — cicpType encoding**

Byte position	Field length (bytes)	Content	Encoded as
0 to 3	4	'cicp' (63696370h) type signature	
4 to 7	4	Reserved, shall be set to 0	
8	1	ColourPrimaries	uint8Number
9	1	TransferCharacteristics	uint8Number
10	1	MatrixCoefficients	uint8Number
11	1	VideoFullRangeFlag	uint8Number

The fields ColourPrimaries, TransferCharacteristics, MatrixCoefficients, and VideoFullRangeFlag shall be encoded as specified in Recommendation ITU-T H.273. Recommendation ITU-T H.273 provides detailed descriptions of the code values and their interpretation.

NOTE: Recommendation ITU-T H.273 describes the fields as follows:

The field ColourPrimaries indicates the chromaticity coordinates of the source colour primaries in terms of the CIE 1931 definition of x and y as specified by ISO 11664-1.

The field TransferCharacteristics indicates either:

- the reference opto-electronic transfer characteristic function of the source picture as a function of a source input linear optical intensity input with a nominal real-valued range of 0 to 1, or
- the inverse of the reference electro-optical transfer characteristic function as a function of an output linear optical intensity with a nominal real-valued range of 0 to 1.

The field MatrixCoefficients describes the matrix coefficients used in deriving luma and chroma signals from the red, green, and blue, or X, Y, and Z primaries.

The field VideoFullRangeFlag specifies the scaling and offset values applied in association with the MatrixCoefficients, with 0 (zero) indicating “narrow-range” encoding, 1 indicating “full-range” encoding.

#### EXAMPLES:

Examples for RGB images.

When the data colour space in the profile header is RGB, MatrixCoefficients is always 0 (zero) and VideoFullRangeFlag is often 1.

Codes	Interpretation
1-1-0-0	RGB narrow range representation specified in Recommendation ITU-R BT.709-6, Item 3.4
1-13-0-1	RGB full range color encoding specified in IEC 61966-2-1 sRGB
9-14-0-0	R'G'B' narrow range representation specified in Recommendation ITU-R BT.2020-2, Table 5
9-16-0-0	PQ R'G'B' narrow range representation specified in Recommendation ITU-R BT.2100-2, Table 9
9-16-0-1	PQ R'G'B' full range representation specified in Recommendation ITU-R BT.2100-2, Table 9
9-18-0-0	HLG R'G'B' narrow range representation specified in Recommendation ITU-R BT.2100-2
9-18-0-1	HLG R'G'B' full range representation specified in Recommendation ITU-R BT.2100-2

Examples for narrow-range YCbCr or ICtCp images.

When the data colour space in the profile header is YCbCr, MatrixCoefficients is always non-zero, and VideoFullRangeFlag is usually 0 (zero). ICtCp images use the YCbCr data colour space in the profile header.

Codes	Interpretation
1-1-1-0	YCbCr representation specified in Recommendation ITU-R BT.709-6, Item 3.4
9-14-9-0	Y'Cb'Cr' narrow range representation specified in Recommendation ITU-R BT.2020-2, Table 5
9-16-9-0	PQ Y'Cb'Cr' narrow range representation specified in Recommendation ITU-R BT.2100-2, Table 9
9-16-14-0	PQ ICtCp narrow range representation specified in Recommendation ITU-R BT.2100-2, Table 9
9-18-9-0	HLG Y'Cb'Cr' narrow range representation specified in Recommendation ITU-R BT.2100-2
9-18-14-0	HLG ICtCp narrow range representation specified in Recommendation ITU-R BT.2100-2

## **Bibliography**

IEC 61966-2-1 + Amd.1, Multimedia systems and equipment – Colour measurement and management – Part 2-1: Colour management – Default RGB colour space – sRGB

Recommendation ITU-R BT.709-6, Parameter values for the HDTV standards for production and international programme exchange

Recommendation ITU-R BT.2020-2, Parameter values for ultra-high definition television systems for production and international programme exchange

Recommendation ITU-R BT.2100-2, Image parameter values for high dynamic range television for use in production and international programme exchange

Supplement 19 to ITU-T H-series Recommendations (10/2019) - Usage of video signal type code points